

**MATERIAL SAFETY DATA SHEET****SECTION 1 - IDENTIFICATION**

**Product identifier** : **Hot 4-in-1 Heating Oil Treatment**

**Product Code(s)** : 00161, 90161, 00164, 90164, 00163  
Canadian Product Codes: 00221,90221

**Product Use** : Fuel oil treatment

**Chemical Family** : Mixture.

**Supplier's name and address:**  
**FPPF Chemical Company, Inc.**  
117 West Tupper Street  
Buffalo, NY, USA  
14201

**Manufacturer's name and address:**  
Refer to Supplier

**Information Telephone #** : 1-800-735-3773

**24 Hr. Emergency Tel #** : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

**SECTION 2 - HAZARDS IDENTIFICATION**

**Classification** : OSHA: Hazardous classification: Combustible liquid; Acute Health Hazard; Chronic Health Hazard.

WHMIS classification: Class B3 (Combustible Liquids); Class D1A (Materials Causing Immediate and Serious Toxic Effects, Very Toxic Material); Class D2A (Materials Causing Other Toxic Effects, Very Toxic Material); Class D2B (Materials Causing Other Toxic Effects, Toxic Material).

**Emergency Overview** : Amber liquid. Odor of mineral springs.  
Warning! Combustible liquid and vapor. Harmful or fatal if inhaled or absorbed through the skin. Causes central nervous system depression. May cause irritation to upper respiratory system. Severe skin and eye irritant. May be fatal if ingested. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal. Contains material which may cause cancer, based on animal data.

**POTENTIAL HEALTH EFFECTS:****Signs and symptoms of short-term (acute) exposure**

*Inhalation* : Harmful or fatal if inhaled. Symptoms may include nausea, vomiting, dizziness, drowsiness and other symptoms of central nervous system depression. May result in unconsciousness and possibly death. May cause irritation to the nose, throat and upper respiratory tract.

*Skin* : May cause moderate to severe skin irritation. May be absorbed and cause symptoms similar to those for inhalation.

*Eyes* : May cause moderate to severe irritation.

*Ingestion* : Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if very large amounts are swallowed. May be absorbed and cause symptoms similar to those for inhalation. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

**Effects of long-term (chronic) exposure**

**Carcinogenic status** : Prolonged or repeated contact may cause drying, cracking and defatting of the skin.  
: Possible cancer hazard. See TOXICOLOGICAL INFORMATION, Section 11.

**Additional health hazards** : See TOXICOLOGICAL INFORMATION, Section 11.

**Potential environmental effects** : See ECOLOGICAL INFORMATION, Section 12.

**SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

<b>Ingredients</b>	<b>CAS #</b>	<b>Wt.%</b>
Mineral spirits	64742-88-7	N/Av
1,2,4-Trimethylbenzene	95-63-6	N/Av

Ethylene glycol monobutyl ether	111-76-2	N/Av
Vinyl acetate	108-05-4	N/Av

**SECTION 4 - FIRST AID MEASURES**

- Inhalation** : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Get medical attention.
- Skin contact** : Remove/Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes. If irritation or symptoms develop, seek medical attention.
- Ingestion** : Seek immediate medical attention/advice. Do not induce vomiting, unless directed to do so by qualified medical personnel. Never give anything by mouth to an unconscious person.
- Notes For Physician** : Treat symptomatically.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Fire hazards/conditions of flammability** : Combustible liquid and vapor. This material may be ignited by heat, sparks and direct flame. Vapours are heavier than air and collect in confined and low-lying areas. Vapour can travel to ignition source and flash back. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.
- Flammability classification (OSHA 29 CFR 1910.1200)** : Combustible Liquid Class III A.
- Oxidizing properties** : None known.
- Explosion data: Sensitivity to mechanical impact / static discharge** : Not expected to be sensitive to mechanical impact or static discharge.
- Suitable extinguishing media** : Dry chemical, foam, carbon dioxide and water fog.
- Special fire-fighting procedures/equipment** : Firefighters should wear proper protective equipment and self contained breathing apparatus with full face piece operated in positive pressure mode. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.
- Hazardous combustion products** : Carbon oxides; Aldehydes; Hydrocarbons; irritating fumes and smoke.
- NFPA Rating** : 0 - Minimal    1 - Slight    2 - Moderate    3 - Serious    4 - Severe  
 : *Health: 3    Flammability: 2    Instability: 0    Special Hazards: 0*

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

- Personal precautions** : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up.
- Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.
- Spill response/cleanup** : Ventilate area of release. Remove all sources of ignition. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.
- Prohibited materials** : Do not use combustible absorbents, such as sawdust.
- Special spill response procedures** : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8002).  
 US CERCLA Reportable quantity (RQ): vinyl acetate (5000 lbs / 2270 kg)

**SECTION 7 - HANDLING AND STORAGE**



<b>Volatile organic Compounds (VOC's)</b>	<b>Volatiles (% by weight)</b>	: Approximately 87%
: N/Av		
<b>Flash point</b>		: >60°C / >140°F
<b>Flash point Method</b>		: Tag closed cup
<b>Lower flammable limit (% by vol.)</b>	<b>Auto-ignition temperature</b>	: N/Av
: N/Av	<b>Upper flammable limit (% by vol.)</b>	: N/Av
<b>Flame Projection Length</b>	<b>Flashback observed</b>	: N/Av
: N/Av		

**Section 10: Stability And Reactivity**

<b>Stability and reactivity</b>	: Stable under the recommended storage and handling conditions prescribed.
<b>Hazardous polymerization</b>	: Will not occur.
<b>Conditions to avoid</b>	: Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas.
<b>Materials To Avoid And Incompatibility</b>	: See Section 7 (Handling and Storage) section for further details.
<b>Hazardous decomposition products</b>	: None known, refer to hazardous combustion products in Section 5.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

<b>Target organs</b>	: Eyes, skin, respiratory system, digestive system, central nervous system.
<b>Routes of exposure</b>	: <i>Inhalation:</i> YES <i>Skin Absorption:</i> YES <i>Skin &amp; Eyes:</i> YES <i>Ingestion:</i> YES
<b>Toxicological data</b>	: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Ingredients</u>	<u>LC<sub>50</sub>(4hr)</u>	<u>LD<sub>50</sub></u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Mineral spirits	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	18 g/m <sup>3</sup>	5000 mg/kg	N/Av
Ethylene glycol monobutyl ether	450 ppm/4H	530 mg/kg	400 - 500 mg/kg
Vinyl acetate	3250 - 4100 ppm	2900 mg/kg	2300 mg/kg

<b>Carcinogenic status</b>	: Contains ethylene glycol monobutyl ether. Ethylene glycol monobutyl ether is classified as a confirmed animal carcinogen by ACGIH (Group A3). Contains vinyl acetate. Vinyl acetate is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).
<b>Reproductive effects</b>	: Not expected to be cause reproductive effects.
<b>Teratogenicity</b>	: Not expected to be a teratogen.
<b>Mutagenicity</b>	: Not expected to be mutagenic in humans.
<b>Epidemiology</b>	: Not available.
<b>Sensitization to material</b>	: Not expected to be a skin or respiratory sensitizer.
<b>Synergistic materials</b>	: Not available.
<b>Irritancy</b>	: Irritating to eyes, respiratory system and skin.
<b>other important hazards</b>	: None known or reported by the manufacturer.
<b>Conditions aggravated by overexposure</b>	: Pre-existing skin, eye, respiratory and central nervous system disorders.



**SECTION 12 - ECOLOGICAL INFORMATION**

<b>Ecotoxicity</b>	: No data is available on the product itself.
<b>Mobility</b>	: No data is available on the product itself.
<b>Persistence</b>	: No data is available on the product itself.
<b>Bioaccumulation potential</b>	: No data is available on the product itself.
<b>Other Adverse Environmental effects</b>	: The ecological characteristics of this product have not been fully investigated. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

- Handling for Disposal** : Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not cut, weld, drill or grind on or near this container.
- Methods of Disposal** : Dispose of in accordance with federal, provincial and local hazardous waste laws.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

**SECTION 14: TRANSPORT INFORMATION**

Regulatory Information	UN Number	Shipping Name	Class	Packing Group	Label
49CFR/DOT	NA1993	Combustible liquid, n.o.s. (Aliphatic naphtha )	Combustible.	III	
<b>49CFR/DOT Additional information</b>	Not regulated for road or rail shipment if packaged in non-bulk containers (450 Litres or less each). The 'label' appearing here is the placard to be used for bulk shipments.				
TDG	None	Not regulated.	Not regulated	none	
<b>TDG Additional information</b>	None.				

**SECTION 15 - REGULATORY INFORMATION**

**US Federal Information:**

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200). See Section 2.

SARA TITLE III: Sec. 302, Extremely Hazardous Substances, 40 CFR 355: No Extremely Hazardous Substances are present in this material.

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Acute Health Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

SARA TITLE III: Sec. 313, Toxic Chemicals Notification, 40 CFR 372: This product may be subject to SARA notification requirements, since it contains Toxic Chemical constituents above their de minimus concentrations. This product contains: 1,2,4-Trimethylbenzene; vinyl acetate

**US State Right to Know Laws:**

California Proposition 65: To the best of our knowledge, this product does not contain any chemicals known to the State of California to cause cancer or reproductive harm.

**International Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). See Section 2.


**This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.**

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating** : \* - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe  
*Health:* \*3 *Flammability:* 2 *Reactivity:* 0

- Legend** :
- ACGIH: American Conference of Governmental Industrial Hygienists
  - CAS: Chemical Abstract Services
  - CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
  - CFR: Code of Federal Regulations
  - DOT: Department of Transportation
  - EPA: Environmental Protection Agency
  - HMIS: Hazardous Materials Identification System
  - HSDB: Hazardous Substances Data Bank
  - IARC: International Agency for Research on Cancer
  - Inh: Inhalation
  - MSHA: Mine Safety and Health Administration
  - N/Ap: Not Applicable
  - N/Av: Not Available
  - NFPA: National Fire Protection Association
  - NIOSH: National Institute of Occupational Safety and Health
  - NTP: National Toxicology Program
  - OSHA: Occupational Safety and Health Administration
  - PEL: Permissible exposure limit
  - RCRA: Resource Conservation and Recovery Act
  - RTECS: Registry of Toxic Effects of Chemical Substances
  - SARA: Superfund Amendments and Reauthorization Act
  - STEL: Short Term Exposure Limit
  - TDG: Canadian Transportation of Dangerous Goods Act & Regulations
  - TLV: Threshold Limit Values
  - TPQ: Threshold Planning Quantity
  - TSCA: Toxic Substance Control Act
  - TWA: Time Weighted Average
  - WHMIS: Workplace Hazardous Materials Identification System

- References** :
1. ACGIH, Threshold Limit Values and Biological Exposure Indices for 2009
  2. International Agency for Research on Cancer Monographs, searched 2009
  3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases (Chempendium, HSDB and RTECs).
  4. Material Safety Data Sheet from manufacturer.
  5. US EPA Title III List of Lists
  6. California Proposition 65 List

<p><b><u>Prepared for:</u></b>          FPPF Chemical Company, Inc.          117 West Tupper Street          Buffalo, NY, USA 14201          Telephone: 1-800-735-3773          Please direct all enquiries to FPPF Chemical Company</p>	
<p><b><u>Prepared by:</u></b>          ICC The Compliance Center Inc.  <a href="http://www.thecompliancecenter.com">http://www.thecompliancecenter.com</a></p>	

**DISCLAIMER OF LIABILITY**

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc using information provided by / obtained from FPPF Chemical Company, Inc and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc and FPPF Chemical Company, Inc.

**Preparation Date (dd/mm/yyyy)** : 03/01/2013