

1-800-735-3773 www.fppf.com

Remove Water, Increase Mileage, Reduce Wear

20)WER

Works with **Biofuels**



Fuel Power is a unique formulation of organic compounds for use YEAR 'ROUND in all Diesel, Gasoline, Aq, and Marine fuels to prevent damage, wear, and premature failure.







Water damages injectors, scores pintles, creates gum and varnish, interferes with fuel combustion and serves as a breeding ground for bacteria and fungi. Fuel Power contains the most effective combination of ingredients that bonds with Hydrogen in the water to create a combustible liquid that burns with the fuel. It prevents damage, wear and premature fuel pump failure, improves combustion and mileage, stabilizes your fuel and prevents sludge. When you want more power out of your diesel fuel, regularly treat with FPPF Fuel Power.



- Alcohol Free
- Use in both Gas & Diesel Fuel
- Hydrogen Polar Bonding
- Eliminates Water
- Increased Fuel Economy
- More Power
- Combustion Catalyst
- Reduces Emissions
- Lubricates Fuel System (Meets HFRR)
- Cleans the Injector System
- Removes Gum & Varnish
- Helps stablize fuel
- Can be used for Fuel Storage
- Controls Icing
- Helps control Waxing and Gelling

Perfect For:





Can be used year 'round in any gas or diesel internal combustion engine. Effective for bulk treating. Can be used for fuel storage as a stabilizer.

FUEL POWER Product Data Sheet

Treat and eliminate water in Diesel Fuel, Home Heating Oil, Kerosene, Bunker Fuel and Gasoline

- Dissolves gum and varnish
- Cleans injector tips
- Restores proper injector spray pattern
 Increases miles per gallon
- Improves combustion efficiency
- Adds power

100% ACTIVE INGREDIENTS

Fuel Power is a concentrated Diesel & Gas **Fuel Treatment**



DIRECTIONS: Add prior to filling for best mixing results.

Fuel Power handles it's own weight in water. 8 ounces of Fuel Power will get rid of 8 ounces of water in gas or diesel. Note: you must treat the heavy water and the suspended water in the fuel. Initial treatment should be a double dose of Fuel Power. If using as a stabilizer - you should double dose at a minimum depending on length of storage.

Each ounce of Fuel Power will treat approximately 15-1/2 gallons of fuel. You can use the entire contents of bottle in your car or pick up truck without concern.

- For Heavy Duty applications, use eight ounces to 120 gallons for the first two treatments.
- Eight ounces to 240 gallons of diesel fuel keeps injectors clean.
- Use eight ounces to 120 gallons in Marine or other extremely wet conditions.

In very cold weather use FPPF Polar Power or FPPF Total Power to prevent icing and gelling of diesel fuel.

Can be used in any internal combustion engine:

- Heavy Duty Truck
- Medium Duty Truck
- Light Duty Truck
- Cars & Utility Vehicles
- **Construction Equipment**
- Agricultural Equipment
- Marine Applications
- ATV's & UTV's
- Motorcycles
- Tractors
- Lawn Mowers
- Generators
- Chain Saws
- Weed Whackers
- Bulk Tanks

Item #	Unit Size	Treats up To	Case #	Qty/Cs	Case Weight	Cases/Palllet
00099	8 oz. (236 ml)	240 gl. (908 L)	90099	24	14	96
00102PC	5 gl. (18.9 L)	19200 gl. (72680 L)		1	42	36

For more information consult the Safety Data Sheet for this product. All used and unused products should be disposed of in accordance with local, state and federal regulations.

Fuel Power Fm. No. 04000-CA 6/24

