



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

SAFETY DATA SHEET

Hazard statement(s)

Flammable liquid and vapor.
May cause respiratory irritation.
May cause drowsiness and dizziness.
May be fatal if swallowed and enters airways.
Suspected of causing cancer.
Suspected of damaging the unborn child.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking
Ground and bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment.
Use non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing vapors or mists.
Use only outdoors or in a well-ventilated area.
Wash hands and face thoroughly after handling.
Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
In case of fire: Use water fog, dry chemical, CO₂ or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Store locked up. Keep cool. Keep container tightly closed.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification: Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Light aromatic solvent naphtha	Aromatic solvent naphtha Solvent Naphtha (Petroleum) Light Aromatic	64742-95-6	45.0 - 70.0
Dipropylene glycol methyl ether	1- (2-Methoxypropoxy)-2-propanol DPGME	34590-94-8	10.0 - 30.0
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	1.0 - 5.0
1,3,5-Trimethyl benzene	Trimethylbenzol Mesitylene	108-67-8	1.0 - 5.0
Trimethylbenzenes	Trimethylbenzene (mixed isomers) Methylxylenes	25551-13-7	1.0 - 5.0
Xylene	Dimethylbenzene; Methyltoluene; Xylol	1330-20-7	1.0 - 5.0



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 3 of 14

SAFETY DATA SHEET

Cumeme	Isopropyl benzene	98-82-8	0.1 - 1.0
--------	-------------------	---------	-----------

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration.
- Skin contact* : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: get medical advice/attention.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.
- Suspected of causing cancer. Suspected of damaging the unborn child. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. Aspiration hazard.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable liquid and vapor. Keep away from heat, sparks and open flames. After prolonged storage, may release explosive peroxides in the presence of air. Vapors may travel considerable distance to a source of ignition and flash back. Vapours may be heavier than air and may collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquids - Category 3

Hazardous combustion products

- : Carbon oxides, Other irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters



SAFETY DATA SHEET

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

- Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the National Response Center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): See section 15.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Avoid breathing mist or vapor. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

- Conditions for safe storage** : Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store away from incompatibles and out of direct sunlight. After prolonged storage, may release explosive peroxides in the presence of air. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

- Incompatible materials** : Strong oxidizing agents; Acids; Bases.



SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
Dipropylene glycol methyl ether	100 ppm (skin)	150 ppm (skin)	100 ppm (600 mg/m ³) (skin)	N/Av
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
Trimethylbenzenes	25 ppm	N/Av	25 ppm (final rule limit)	N/Av
Xylene	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
Cumeme	50 ppm	N/Av	50 ppm (245 mg/m ³) (Skin)	N/Av

Exposure controls

Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

- : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

- : Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not eat, drink, smoke or use cosmetics while working with this product. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State

- : Liquid.



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 6 of 14

SAFETY DATA SHEET

Colour : Straw
Odour : Solvent odor.
Odour threshold : N/Av
pH : N/Av
Melting Point/Freezing point : N/Av

Initial boiling point and boiling range

: >149°C / >300°F

Flash point : 48°C / 118.4°F

Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : N/Av

Flammability : Flammable.

Lower explosion or flammability limit (% by vol.)

: N/Av

Upper explosion or flammability limit (% by vol.)

: N/Av

Oxidizing properties : None.

Explosive properties : N/Av

Vapour pressure : N/Av

Relative vapour density : N/Av

Relative density / Specific gravity

: 0.88-0.91

Solubility in water : N/Av

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : N/Av

Particle characteristics : N/Av

Volatiles (% by weight) : N/Av

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : N/Av

Other physical/chemical comments

: None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization will not occur.

Conditions to avoid : Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.

Incompatible materials : Strong oxidizing agents; Acids; Bases..

Hazardous decomposition products

: None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 7 of 14

SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption
: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : Inhalation may cause respiratory irritation and central nervous system depression. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Sign and symptoms ingestion

- : Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.

Sign and symptoms skin

- : Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes

- : Direct eye contact may cause slight or mild, transient irritation.

Potential Chronic Health Effects

- : Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification :Carcinogenicity- Category 2 Suspected of causing cancer. Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B).

Reproductive effects & Teratogenicity

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification Reproductive Toxicity-Category 1 Suspected of damaging the unborn child. (Developmental) Contains Xylene (mixed isomers) Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.

Sensitization to material

- : Not expected to be a skin or respiratory sensitizer.



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 8 of 14

SAFETY DATA SHEET

Specific target organ effects : Eyes, skin, respiratory system, digestive system, central nervous system, blood system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification
 Specific target organ toxicity, single exposure Category 3
 May cause drowsiness and dizziness.
 May cause respiratory irritation.

Not classified as specific target organ toxicity-repeated exposure.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None reported by the manufacturer.

Toxicological data

: The calculated ATE values for this mixture are:
 ATE inhalation (vapours) =23.53 mg/L/4H

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg
Dipropylene glycol methyl ether	> 3 mg/L (mist) (No mortality)	5120 mg/kg	9480 mg/kg
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethyl benzene	24 mg/L	23 000 mg/kg	>3160mg/kg
Trimethylbenzenes	18 - 24 mg/L (vapour)	8970 mg/kg	> 3160 mg/kg
Xylene	6350 ppm (27.6 mg/L) (vapour)	3253 mg/kg	12 180 mg/kg
Cumeme	8000 ppm (39 mg/L) (vapour)	2260 mg/kg	10 627 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Toxic to aquatic life with long lasting effects. No data is available on the product itself. See the following tables for individual ingredient ecotoxicity data.



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

SAFETY DATA SHEET

Ecotoxicity data:

<u>Ingredients</u>	CAS #	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.
Dipropylene glycol methyl ether	34590-94-8	> 10,000 mg/L (Fathead minnow)	N/Av	None.
1,2,4-Trimethylbenzene	95-63-6	7.72 mg/L (Fathead minnow)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.
Trimethylbenzenes	25551-13-7	7.72 mg/L (Fathead minnow) (Read-across)	N/Av	None.
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Cumeme	98-82-8	4.8 mg/L (Rainbow trout)	N/Av	None.

<u>Ingredients</u>	CAS #	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.
Dipropylene glycol methyl ether	34590-94-8	1919 mg/L (Daphnia magna)	≥ 0.5 mg/L	None.
1,2,4-Trimethylbenzene	95-63-6	3.6 mg/L (Daphnia magna)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna)	0.4mg/L	None.
Trimethylbenzenes	25551-13-7	2.7 mg/L (Daphnia magna) (Read-across)	0.4 mg/L (Read-across)	None.
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Cumeme	98-82-8	4 mg/L/24hr (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS #	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av
Dipropylene glycol methyl ether	34590-94-8	> 969 mg/L/72hr (Green algae)	969 mg/L/72hr	None.
1,2,4-Trimethylbenzene	95-63-6	2.356mg/L/96hr QSAR	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	3.191mg/L QSAR	N/Av	None.
Trimethylbenzenes	25551-13-7	5.7 mg/L/72hr (Green algae) (Read-across)	0.38 mg/L/72hr (Read-across)	None.
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Cumeme	98-82-8	2.6 mg/L/72hr (Green algae)	N/Av	None.



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 10 of 14

SAFETY DATA SHEET

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

: No data is available on the product itself.

See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Light aromatic solvent naphtha	2.1 - 6(calculated)	10 - 2500
1,2,4-Trimethylbenzene	3.78	31 - 275
1,3,5-Trimethyl benzene	3.6 - 3.93	23 - 328
Xylene	3.12 - 3.2	50 - 58
Cumene	3.55	224 (calculated)
Trimethylbenzenes	3.63	42 - 328 (common carp)
Dipropylene glycol methyl ether	0.0061	< 1

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

: The ecological characteristics of this product have not been fully investigated.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.







Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 11 of 14

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha)	3	III	
49CFR/DOT Additional information	This material may be reclassified as a 'Combustible liquid', when shipping by ground within the United States only. Combustible liquids may be shipped as non-hazardous material when shipped in non-bulk containers (450 L / 119 Gallons or less). Refer to 49 CFR Section 173.150. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha)	3	III	
TDG Additional information	This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
ICAO/IATA	UN1993	Flammable liquid, n.o.s. (Aromatic Naphtha)	3	III	
ICAO/IATA Additional information	Refer to ICAO/IATA Packing Instruction				
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic Naphtha)	3	III	
IMDG Additional information	Consult the IMDG regulations for exceptions.				

Special precautions for user : Keep away from heat, sparks and open flame - No smoking.

Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

SAFETY DATA SHEET

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de Minimis Concentration
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	No
Dipropylene glycol methyl ether	34590-94-8	Yes	None.	None.	No	No
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	No
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Av	No	No
Trimethylbenzenes	25551-13-7	Yes	None.	None.	No	N/Ap
Xylene	1330-20-7	Yes	100 lbs / 45.4 kg	None.	Yes	1%
Cumeme	98-82-8	Yes	5000 lb/ 2270 kg	None.	Yes	1%

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable ;Specific target organ toxicity, single exposure ;Carcinogenicity; Reproductive toxicity ;Aspiration hazard .

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No
Dipropylene glycol methyl ether	34590-94-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No
Trimethylbenzenes	25551-13-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Xylene	1330-20-7	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Cumeme	98-82-8	Yes	Cancer	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 13 of 14

SAFETY DATA SHEET

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
Dipropylene glycol methyl ether	34590-94-8	252-104-2	Present	Present	(7)-97; (2)-426	KE-12230	Present	HSR001402
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
Trimethylbenzenes	25551-13-7	247-099-9	Present	Present	(3)-7; (3)-3427	KE-34408	Present	May be used as a component in a product covered by a group standard, but is not approved for use as a chemical in its own right.
Xylene	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Cumeme	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
ATE: Acute Toxicity Estimate
AICS: Australian Inventory of Chemical Substances
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CNS: Central Nervous System
CSA: Canadian Standards Association
DOT: Department of Transportation
EC50: Effective Concentration 50%
EINECS: European Inventory of Existing Commercial chemical Substances
ENCS: Existing and New Chemical Substances
EPA: Environmental Protection Agency
IARC: International Agency for Research on Cancer
IMDG: International Maritime Dangerous Goods
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
NOEC: No observable effect concentration
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances



Polar Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 03/29/2024

Page 14 of 14

SAFETY DATA SHEET

SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

Preparation Date (mm/dd/yyyy)

: 04/24/2020

Reviewed Date SDS (dd/mm/yyyy)

: 29/03/2024

Revision No.

: 2

Revision Information

: 1. IDENTIFICATION 9. PHYSICAL AND CHEMICAL PROPERTIES

DISCLAIMER

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process. This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of FPPF Chemical Company, Inc.

END OF DOCUMENT