

Page 1 of 15

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: Total Power

Other means of identification: 90316

Recommended use of the chemical and restrictions on use

: Diesel fuel treatment Restriction on use: None known . Chemical family : Mixture. Name, address, and telephone number of the supplier: FPPF Chemical Company, Inc. 100 Dingens St. Buffalo, NY, USA 14206 Supplier's Telephone # : (800) 735-3773 24 Hr. Emergency Tel # : PERS: North America 1-800-633-8253; International: +1-801-629-0667 Contract number: 8027

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear to slightly hazy amber liquid. Solvent odor.

Most important hazards: Flammable liquid and vapor. May be ignited by open flames and sparks. Aspiration hazard. May cause respiratory irritation. May cause drowsiness or dizziness. Possible cancer hazard - contains material which may cause cancer.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification: Flammable liquid- Category 3 Carcinogen - Category 2 Specific target organ toxicity, single exposure - Category 3 (narcotic effects) Specific target organ toxicity, single exposure - Category 3 (respiratory) Aspiration Toxicity - Category 1

Label elements

Hazard pictogram(s)





Page 2 of 15

SAFETY DATA SHEET

Hazard statement(s)

Flammable liquid and vapor. Suspected of causing cancer. May cause respiratory irritation. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

Precautionary statement(s)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors or mists. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

May be sensitive to static discharge. Burning produces obnoxious and toxic fumes.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	Common name and synonyms	<u>CAS #</u>	Concentration (% by weight)
Light aromatic solvent naphtha	Aromatic solvent naphtha Solvent Naphtha (Petroleum) Light Aromatic	64742-95-6	30.0 - 60.0
Dipropylene glycol monomethyl ether	DPGME	34590-94-8	10.0 - 30.0
Heavy aromatic solvent naphtha	Aromatic solvent naphtha Heavy Aromatic Naphtha	64742-94-5	1.0 - 5.0
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	1.0 - 5.0
1,3,5-Trimethyl benzene	Mesitylene Trimethylbenzol	108-67-8	1.0 - 5.0
2-Ethylhexyl nitrate	Nitric acid, 2-ethylhexyl ester Ethylhexyl nitrate	27247-96-7	1.0 - 5.0



Page 3 of 15

SAFETY DATA SHEET

Naphthalene	Moth balls Moth flakes Tar camphor	91-20-3	0.1 - 1.0
2-ethyl hexanol	2-ethylhexan-1-ol 2-Ethylhexyl alcohol 2EH	104-76-7	0.1 - 1.0
Гhe Solvent naphtha (petroleum) he following chemicals:	, heavy aromatic component cont	ains	
Cumene	Isopropyl benzene; Cumol, 2-Phenyl propane	98-82-8	<0.1
1,2,3-Trimethylbenzene	Benzene, 1,2,3-trimethyl-	526-73-8	<0.1
Xylene (mixed isomers)	Dimethylbenzene Methyltoluene Xylol	1330-20-7	<0.1
trimethylbenzene	Trimethylbenzene (mixed isomers) Methylxylenes	25551-13-7	<0.1

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion	: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Aspiration hazard. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.				
Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.				
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: get medical advice/attention.				
Eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.				
Most important symptoms and effects, both acute and delayed					
	: May be fatal if swallowed and enters airways.Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.Symptoms include coughing, shortness of breath and wheezing. May cause respiratory irritation.Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.				
	Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.				
Indication of any immedia	te medical attention and special treatment needed				
	: Treat symptomatically.				

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Dry chemical, foam, carbon dioxide and water fog.

Unsuitable extinguishing media

: Do not use a solid water stream as it may scatter and spread fire.



Page 4 of 15

SAFETY DATA SHEET

Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable liquid and vapour. Vapours may be heavier than air and may collect in confined and low-lying areas. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 3

Hazardous combustion products

: Carbon oxides. Polycyclic aromatic hydrocarbons. Reactive hydrocarbons. Nitrogen oxides. Aldehydes. Other irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Environmental precautions	 Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8. Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply. 			
Methods and material for containment and cleaning up				
	: Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools.For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.			
Special spill response proce	dures			
	 If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the National Response Center in the United States (phone: 1-800-424-8802) 			

- (phone: 1-800-424-8802).
- ÜS CERCLA Reportable quantity (RQ): See section 15.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling



r

Total Power SDS Revision Date (mm/dd/yyyy): 03/23/2024

Page 5 of 15

SAFETY DATA SHEET

	:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Avoid breathing mist or vapours. Wash thoroughly after handling. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.
Conditions for safe storage		up. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
Incompatible materials	:	Strong oxidizing agents, Perchloric acid, Bases .

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:						
Chemical Name	ACGIH	ACGIH TLV		OSHA PEL		
	TWA	<u>STEL</u>	PEL	<u>STEL</u>		
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av		
Dipropylene glycol monomethyl ether	100 ppm (skin)	150 ppm (skin)	100 ppm (600 mg/m³) (skin)	N/Av		
Heavy aromatic solvent naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av		
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av		
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av		
2-Ethylhexyl nitrate	N/Av	N/Av	N/Av	N/Av		
Naphthalene	10 ppm (skin)	N/Av	10 ppm ; 50 mg/m ³	15ppm; 75mg/m ²		
Cumene	50 ppm	N/Av	50 ppm ; 245 mg/m³ (Skin)	N/Av		
2-ethyl hexanol	N/Av	N/Av	N/Av	N/Av		
1,2,3-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	N/Av	N/Av		
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm (435 mg/m³)	N/Av		
trimethylbenzene	25 ppm	N/Av	25 ppm (final rule limit)	N/Av		

Exposure controls

Ventilation and engineering measures



Page 6 of 15

SAFETY DATA SHEET

Respiratory protection	 Use explosion-proof electrical and ventilating equipment. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment. If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
Skin protection	: Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye / face protection	: Wear eye/face protection. Safety glasses with side-shields or chemical splash goggles, depending on workplace standards.
Other protective equipment	: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
General hygiene consideration	ns
	: Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	:	Liquid.			
Colour	:	Amber			
Odour	:	Solvent odor.			
Odour threshold	:	N/Av			
рН	:	N/Av			
Melting Point/Freezing point	:	N/Av			
Initial boiling point and boilin	g	range			
• •		>149°C / 300°F			
Flash point	:	48.3°C / 119°F			
Flashpoint (Method)	•	Tag closed cup			
Evaporation rate (BuAe = 1)					
Flammability	:	N/Ap			
Lower explosion or flammabi	114-	•			
	:				
Upper explosion or flammability limit (% by vol.)					
	:	N/Av			
Oxidizing properties	:	None known.			
Explosive properties	:	N/Av			
Vapour pressure	:	<4mm Hg @ 20°C			
Relative vapour density	:	>1			
Relative density / Specific gra	avi	ity			
	:	0.891			
Solubility in water	:	Partially soluble.			
Other solubility(ies)	:	N/Av			
Partition coefficient: n-octand	ol/	water or Coefficient of water/oil distribution			
	:	N/Av			
Auto-ignition temperature	:	N/Av			
Decomposition temperature		N/Av			
• •	-				



Page 7 of 15

SAFETY DATA SHEET

Viscosity	:	N/Av	
Particle characteristics	:	N/Ap	
Volatiles (% by weight)	:	90%(approximately)	
Volatile organic Compounds	(V	OC's)	
	:	N/Av	
Absolute pressure of container			
	:	N/Ap	
Flame projection length	:	N/Ap	
Other physical/chemical comments			
	:	None reported by the manufacturer.	
SECTION 40 STABILIT	v		

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not normally reactive.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous rea	ctio	ons
	:	Hazardous polymerization will not occur.
Conditions to avoid	:	Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.
Incompatible materials	:	Strong oxidizing agents, Perchloric acid, Bases.
Hazardous decomposition p	roc	lucts
	:	None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation	:	YES		
Routes of entry skin & eye	:	YES		
Routes of entry Ingestion	:	YES		
Routes of exposure skin absorption				

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

Sign and symptoms ingestio	: n	Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowiness, slurred speech, nausea, and possible nervous system depression.
	:	Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways.Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.
Sign and symptoms skin	:	May cause drying or defatting of the skin.
Sign and symptoms eyes	:	Direct eye contact may cause slight or mild, transient irritation.
Potential Chronic Health Effe	ect	S
	:	Prolonged or repeated contact may cause drying, cracking and defatting of the skin.
Mutagenicity		Not expected to be mutagenic in humans.



Page 8 of 15

SAFETY DATA SHEET

Carcinogenicity	:	Carcinogen - Category 2 . Suspected of causing cancer.
Reproductive effects & Terat	tog	Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated). Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B). enicity
	:	Not classifiable as a reproductive toxin.
Sensitization to material	:	Not expected to be a skin sensitizer. Not expected to be a respiratory sensitizer.
Specific target organ effects	:	
Medical conditions aggravat	ho	Not classified as specific target organ toxicity-repeated exposure.
medical conditions aggravat		
Synergistic materials		Pre-existing skin, eye, respiratory and central nervous system disorders. None reported by the manufacturer.
, ,	•	
Toxicological data	:	The calculated ATE values for this mixture are:

ATE inhalation (vapours) =35.06mg/L/4H

See below for individual ingredient acute toxicity data.

	LC50(4hr)	L	D 50
<u>Chemical name</u>	inh, rat	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg
Dipropylene glycol monomethyl ether	> 3 mg/L (mist) (No mortality)	5120 mg/kg	9480 mg/kg
Heavy aromatic solvent naphtha	> 17.1 mg/L/4 hours	> 6000 mg/kg	> 3160 mg/kg
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethyl benzene	24 mg/L (vapour)	23 000 mg/kg	> 3160 mg/kg
2-Ethylhexyl nitrate	> 14 mg/L	> 9600 mg/kg	> 4800 mL/kg
Naphthalene	No information available.	490 mg/kg	>20,000 mg/kg
2-ethyl hexanol	≥ 1.2, < 5.3 mg/L (aerosol)	2052 mg/kg	> 3000 mg/kg (No mortality)
he Solvent naphtha (pe	etroleum), heavy aromatic comp	onent contains the fo	llowing chemicals:
Cumene	8000 ppm; (39 mg/L) (vapor)	2260 mg/kg	10 627 mg/kg
1,2,3-Trimethylbenzene	N/Av	N/Av	N/Av
Xylene (mixed isomers)	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
trimethylbenzene	18 - 24 mg/L (vapour)	8970 mg/kg	> 3160 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

- Ecotoxicity
- : Toxic to aquatic life with long lasting effects. See the following tables for individual ingredient ecotoxicity data.



Page 9 of 15

SAFETY DATA SHEET

Ecotoxicity data:

	<i>"</i>	Toxicity to Fish				
<u>Ingredients</u>	CAS #	LC50 / 96h	NOEC / 21 day	M Factor		
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.		
Dipropylene glycol monomethyl ether	34590-94-8	> 10,000 mg/L (Fathead minnow)	N/Av	None.		
Heavy aromatic solvent naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.		
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.		
1,2,4-Trimethylbenzene	95-63-6	7.72 mg/L (Fathead minnow)	N/Av	None.		
2-Ethylhexyl nitrate	27247-96-7	2 mg/L (Zebra fish)	2 mg/L (Zebra fish) N/Av			
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	on) 0.12mg/L (40 days) (pink salmon)			
Cumene	98-82-8	4.5 mg/L (Rainbow trout)				
2-ethyl hexanol	104-76-7	17.1 mg/L (Golden orfe)	7.1 mg/L (Golden orfe) N/Av			
Xylene (mixed isomers)	1330-20-7	8.2 mg/L (Rainbow trout) N/Av		None.		
trimethylbenzene	25551-13-7	7.72 mg/L (Fathead minnow) (Read-across)	N/Av	None.		

Ingredients	CAS #	Тохі	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor	
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.	
Dipropylene glycol monomethyl ether	34590-94-8	1919 mg/L (Daphnia magna)	≥ 0.5 mg/L	None.	
Heavy aromatic solvent naphtha	64742-94-5	1.1 mg/L Water flea	N/Av	None.	
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna) 0.4mg/L		None.	
1,2,4-Trimethylbenzene	95-63-6	3.6mg/L (Daphnia N/Av magna)		None.	
2-Ethylhexyl nitrate	27247-96-7	> 12.6 mg/L (Daphnia magna)			
Naphthalene	91-20-3	3.4 mg/L/ Water flea 0.6mg/L		None.	
Cumene	98-82-8	2.14 mg/L/24hr (Daphnia 0.35mg/L magna)		None.	
2-ethyl hexanol	104-76-7	39 mg/L (Daphnia N/Av magna)		None.	
Xylene (mixed isomers)	1330-20-7	3.2 - 9.56 mg/L (Daphnia N/Av magna)		None.	
trimethylbenzene	25551-13-7	2.7 mg/L (Daphnia magna) (Read-across)	0.4 mg/L (Read-across)	None.	



FPPF Chemical Company, Inc. 100 Dingens St. Buffalo, NY, USA, 14206 Telephone: (800) 735 3773

Total Power SDS Revision Date (mm/dd/yyyy): 03/23/2024

Page 10 of 15

SAFETY DATA SHEET

Ingredients	CAS #	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av		
Dipropylene glycol monomethyl ether	34590-94-8	> 969 mg/L/72hr (Green algae)	969 mg/L/72hr	None.		
Heavy aromatic solvent naphtha	64742-94-5	7.2 mg/L/72 hours (Green algae)				
1,3,5-Trimethyl benzene	108-67-8	3.191 mg/L/96hr (Green N/Av algae) (QSAR)		None.		
1,2,4-Trimethylbenzene	95-63-6	2.356mg/L/96hr QSAR N/Av		None.		
2-Ethylhexyl nitrate	27247-96-7	1.57 mg/L/72hr (Green 12.6 mg/L/72hr algae)		None.		
Naphthalene	91-20-3	0.4mg/L/72hr (Marine diatom)				
Cumene	98-82-8	1.29 mg/L/72br (Green 0.73mg/L algae)		None.		
2-ethyl hexanol	104-76-7	11.5 mg/L/72hr (Green N/Av algae)		None.		
Xylene (mixed isomers)	1330-20-7			None.		
trimethylbenzene	25551-13-7	5.7 mg/L/72hr (Green algae) (Read-across)	0.38 mg/L/72hr (Read-across)	None.		

Persistence and degradability

: No data is available on the product itself.

: No data is available on the product itself.

Bioaccumulation potential

See the following data for ingredient information.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF		
Light aromatic solvent naphtha	2.1 - 6(calculated)	10 - 2500		
Naphthalene	3.7	427		
1,2,4-Trimethylbenzene	3.78	31 - 275		
Xylene (mixed isomers)	3.12 - 3.2	50 - 58		
Heavy aromatic solvent naphtha	2.9 - 6.1	No information available.		
1,3,5-Trimethyl benzene	3.6 - 3.93	23 - 328		
2-Ethylhexyl nitrate	5.24	No information available.		
trimethylbenzene	3.63	42 - 328		
Cumene	3.55 at 23 °C	224		
Dipropylene glycol monomethyl ether	0.0061	< 1		
2-ethyl hexanol	2.9	30		

Mobility in soil

: No data is available on the product itself.



Page 11 of 15

SAFETY DATA SHEET

Other Adverse Environmental effects

: The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal	: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
Methods of Disposal	 Dispose in accordance with all applicable federal, state, provincial and local regulations.
RCRA	: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha)	3	III	3
49CFR/DOT Additional information	49 CFR Section	br road or rail shipment if packaged in non-bulk containers n 173.150. eets the criteria for an environmentally hazardous materia			
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha; Trimethylbenzene)	3	III	
TDG Additional information	the requiremen	ay be shipped as non-regulated material when in small m ts of TDG section 1.33 are met.		,	<i>,</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
		eets the criteria for an environmentally hazardous materia	i according to ti		ae.
ICAO/IATA	UN1993	Flammable liquid, n.o.s. (Aromatic Naphtha)	3		
	UN1993	-	-		de.
ICAO/IATA ICAO/IATA Additional	UN1993	Flammable liquid, n.o.s. (Aromatic Naphtha)	-		

Special precautions for user : Keep away from heat, sparks and open flame - No smoking.
 Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.



Page 12 of 15

SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>		TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
	CAS #	Inventory	Quantity(RQ) (40 CFR 117.302):	Hazardous Substance, 40 CFR 355:	Toxic Chemical	de Minimis Concentration	
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	No	
Dipropylene glycol monomethyl ether	34590-94-8	Yes	None.	None.	No	No	
Heavy aromatic solvent naphtha	64742-94-5	Yes	N/Ap	N/Av	No	No	
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Ap	No	No	
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	No	
2-Ethylhexyl nitrate	27247-96-7	Yes	N/Ap	N/Ap	No	No	
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	N/Av	Yes	Yes	
Cumene	98-82-8	Yes	5000 lb/ 2270 kg	N/Ap	Yes	No	
2-ethyl hexanol	104-76-7	Yes	None.	None.	No	No	
1,2,3-Trimethylbenzene	526-73-8	Yes	N/Ap	N/Av	No	No	
Xylene (mixed isomers)	1330-20-7	Yes	100 lb/ 45.4 kg	N/Ap	Yes	No	
trimethylbenzene	25551-13-7	Yes	N/Ap	N/Ap	No	No	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable ; Aspiration hazard; Specific target organ toxicity, single exposure ; Carcinogenicity .

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:



FPPF Chemical Company, Inc. 100 Dingens St. Buffalo, NY, USA, 14206 Telephone: (800) 735 3773

Total Power SDS Revision Date (mm/dd/yyyy): 03/23/2024

Page 13 of 15

SAFETY DATA SHEET

Ingradiante	CAS #	Californ	State "Right to Know" Lists						
<u>Ingredients</u>	CAS#	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No
Dipropylene glycol monomethyl ether	34590-94-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Heavy aromatic solvent naphtha	64742-94-5	No	Not listed	No	No	No	No	No	No
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
2-Ethylhexyl nitrate	27247-96-7	No	Not listed	No	No	No	No	No	No
Naphthalene	91-20-3	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
Cumene	98-82-8	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
2-ethyl hexanol	104-76-7	No	N/Ap	No	Yes	No	No	Yes	No
1,2,3-Trimethylbenzene	526-73-8	No	N/Ap	No	No	No	No	No	No
Xylene (mixed isomers)	1330-20-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
trimethylbenzene	25551-13-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

International Information:

Components listed below are present on the following International Inventory list:



Page 14 of 15

SAFETY DATA SHEET

Ingredients	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
Dipropylene glycol monomethyl ether	34590-94-8	252-104-2	Present	Present	(7)-97; (2)-426	KE-12230	Present	HSR001402
Heavy aromatic solvent naphtha	64742-94-5	265-198-5	Present	Present	(3)-7	KE-31656	Present	May be used as a single component chemical under an appropriate group standard.
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
2-Ethylhexyl nitrate	27247-96-7	248-363-6	Present	Present	(2)-3598	KE-13803	Present	May be used as a single component chemical under an appropriate group standard.
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
Cumene	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184
2-ethyl hexanol	104-76-7	203-234-3	Present	Present	(2)-217	KE-13766	Present	HSR001386
1,2,3-Trimethylbenzene	526-73-8	208-394-8	Present	Present	(3)-7; (3)-3427	KE-34409	Present	HSR004095
Xylene (mixed isomers)	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
trimethylbenzene	25551-13-7	247-099-9	Present	Present	(3)-7; (3)-3427	KE-34408	Present	May be used as a
								component in a product covered by a group standard, but is not approved for use as a chemical in its own right.

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists ATE: Acute Toxicity Estimate AICS: Australian Inventory of Chemical Substances CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency



FPPF Chemical Company, Inc. 100 Dingens St. Buffalo, NY, USA, 14206 Telephone: (800) 735 3773

Total Power SDS Revision Date (mm/dd/yyyy): 03/23/2024

Page 15 of 15

SAFETY DATA SHEET

IARC: International Agency for Research on Cancer IMDG: International Maritime Dangerous Goods KECI: Korean Existing Chemicals Inventory KECL: Korean Existing Chemicals List LC: Lethal Concentration LD: Lethal Dose N/Ap: Not Applicable N/Av: Not Available NIOSH: National Institute of Occupational Safety and Health NOEC: No observable effect concentration NTP: National Toxicology Program NOEC: No observable effect concentration OECD: Organisation for Economic Co-operation and Development OSHA: Occupational Safety and Health Administration PEL: Permissible exposure limit PICCS: Philippine Inventory of Chemicals and Chemical Substances SARA: Superfund Amendments and Reauthorization Act STEL: Short Term Exposure Limit TDG: Canadian Transportation of Dangerous Goods Act & Regulations TLV: Threshold Limit Values TPQ: Threshold Planning Quantity TSCA: Toxic Substance Control Act TWA: Time Weighted Average

Preparation Date (mm/dd/yyyy)

-	05/02/2023 yy)
:	23/03/2024
:	2
:	9. Physical and chemical properties
	/yy : :

DISCLAIMER

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process. This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of FPPF Chemical Company, Inc.

END OF DOCUMENT