



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 1 of 14

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Hot 4-in-1 Heating Oil Treatment**

Other means of identification : 00221, 90221

Recommended use of the chemical and restrictions on use

: Fuel oil treatment.  
No restrictions on use known.

Chemical family

: Mixture.

Name, address, and telephone number  
of the supplier:

**FPPF Chemical Company, Inc.**

117 West Tupper Street  
Buffalo, NY, USA 14201

Name, address, and telephone number of  
the manufacturer:

Refer to supplier

Supplier's Telephone #

: (800)735-3773

**24 Hr. Emergency Tel #**

: PERS: North America 1-800-633-8253; International: +1-801-629-0667

Contract number: 8027

### SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Amber liquid. Mineral oil odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification

Flammable Liquid - Category 4

Skin Irritation - Category 2

Serious eye damage/eye irritation - Category 2A

Aspiration Toxicity - Category 1

Reproductive toxicity - Category 2

Carcinogenicity- Category 2

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Label elements

Hazard pictogram(s)



Signal Word

**DANGER!**



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 2 of 14

## SAFETY DATA SHEET

*Hazard statement(s)*

Combustible liquid.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness and dizziness.  
May be fatal if swallowed and enters airways.  
Suspected of causing cancer.  
Suspected of damaging the unborn child.

*Precautionary statement(s)*

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from flames and hot surfaces. - No smoking.  
Avoid breathing vapors or mists.  
Use only outdoors or in a well-ventilated area.  
Wash thoroughly after handling.  
Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice.  
IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off contaminated clothing and wash before re-use.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.  
In case of fire: Use water fog, dry chemical, CO<sub>2</sub> or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local regulation.

**Other hazards**

Other hazards which do not result in classification: Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Dipropylene glycol methyl ether	1-(2-Methoxypropoxy) -2-propanol DPGME	34590-94-8	30.0 - 60.0
Light aromatic solvent naphtha	Aromatic Naphtha Solvent naphtha (petroleum) light aromatic	64742-95-6	15.0 - 40.0
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	3.0 - 7.0
1,3,5-Trimethyl benzene	Trimethylbenzol Mesitylene	108-67-8	1.0 - 5.0
Trimethylbenzenes	Methylxylenes (non-specific name); Trimethylbenzenes (non-specific name)	25551-13-7	1.0 - 5.0



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 3 of 14

## SAFETY DATA SHEET

Xylene (mixed isomers)	Dimethylbenzene Methyltoluene Xylol	1330-20-7	1.0 - 5.0
Cumene	Isopropyl benzene Cumol, 2-phenyl propane	98-82-8	0.1 - 1.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

### SECTION 4. FIRST-AID MEASURES

#### Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Rinse mouth. Aspiration hazard Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: get medical advice/attention. Take off immediately all contaminated clothing and wash it before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

#### Most important symptoms and effects, both acute and delayed

- : May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing. Suspected of causing cancer. Suspected of damaging the unborn child. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

##### *Suitable extinguishing media*

- : Dry chemical, foam, carbon dioxide and water fog.

##### *Unsuitable extinguishing media*

- : Do not use a solid water stream as it may scatter and spread fire.

#### Special hazards arising from the substance or mixture / Conditions of flammability

- : Combustible liquid and vapour. Vapors may travel considerable distance to a source of ignition and flash back. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

#### Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquid - Category 4

#### Hazardous combustion products

- : Carbon oxides. Nitrogen oxides. Reactive hydrocarbons. Aldehydes. Other irritating fumes and smoke.

#### Special protective equipment and precautions for firefighters



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 4 of 14

## SAFETY DATA SHEET

### *Protective equipment for fire-fighters*

- : Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

### *Special fire-fighting procedures*

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

### Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

### Special spill response procedures

- : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).  
US CERCLA Reportable quantity (RQ): See section 15.

## SECTION 7. HANDLING AND STORAGE

### Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from flames and hot surfaces. - No smoking. Wear protective gloves/clothing and eye/face protection. Wash hands thoroughly after handling. Avoid breathing mist or vapor. Do not eat, drink or smoke when using this product. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.

**Conditions for safe storage** : Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Take measures to prevent the build up of electrostatic charge. Store away from incompatibles and out of direct sunlight. After prolonged storage, may release explosive peroxides in the presence of air. Direct sunlight or heat may accelerate the release of peroxides. Rate of peroxide formation is not known. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

**Incompatible materials** : Strong oxidizing agents; Acids; Perchloric acid; Reactive metals; Bases.



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 5 of 14

## SAFETY DATA SHEET

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Dipropylene glycol methyl ether	100 ppm (skin)	150 ppm (skin)	100 ppm (600 mg/m <sup>3</sup> ) (skin)	N/Av
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
Trimethylbenzenes	25 ppm	N/Av	25 ppm (final rule limit)	N/Av
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm (435 mg/m <sup>3</sup> )	N/Av
Cumeme	50 ppm	N/Av	50 ppm ; 245 mg/m <sup>3</sup> (Skin)	N/Av

#### Exposure controls

##### Ventilation and engineering measures

- : Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use non-sparking equipment. In case of insufficient ventilation wear suitable respiratory equipment.

##### Respiratory protection

- : If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. Advice should be sought from respiratory protection specialists.

##### Skin protection

- : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

##### Eye / face protection

- : Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.

##### Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

##### General hygiene considerations

- : Avoid breathing mist or vapor. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Amber liquid.
- Odour : Mineral oil odor
- Odour threshold : N/Av
- pH : N/Av



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 6 of 14

## SAFETY DATA SHEET

Melting Point/Freezing point : N/Av

Initial boiling point and boiling range

: 113 - 116 °C / 235 - 240°F

Flash point : >60°C / >140°F

Flashpoint (Method) : Tag closed cup

Evaporation rate (BuAe = 1) : Slower than n-butyl acetate

Flammability (solid, gas) : N/Av

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None.

Explosive properties : N/Av

Vapour pressure : N/Av

Vapour density : >1

Relative density / Specific gravity

: 0.90

Solubility in water : Slightly soluble.

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : N/Av

Volatiles (% by weight) : ~ 87%

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : N/Av

Other physical/chemical comments

: None reported by the manufacturer.

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization will not occur.

Conditions to avoid : Keep away from flames and hot surfaces. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.

Incompatible materials : Strong oxidizing agents; Acids; Perchloric acid; Bases; Reactive metals

Hazardous decomposition products

: None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure:

Routes of entry inhalation : YES



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 7 of 14

## SAFETY DATA SHEET

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption  
: NO

### Potential Health Effects:

#### Signs and symptoms of short-term (acute) exposure

##### *Sign and symptoms Inhalation*

: Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowsiness, slurred speech, nausea, and possible nervous system depression.

##### *Sign and symptoms ingestion*

: Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing.

##### *Sign and symptoms skin*

: Causes skin irritation. Symptoms include: Dryness, itching, cracking, burning, redness and swelling.

##### *Sign and symptoms eyes*

: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

#### Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Mutagenicity

: Not expected to be mutagenic in humans.

#### Carcinogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification Carcinogenicity- Category 2 Suspected of causing cancer.  
Contains Cumene. Cumene is classified as possibly carcinogenic by IARC (Group 2B).

#### Reproductive effects & Teratogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification Reproductive toxicity - Category 2 Suspected of damaging the unborn child.  
Contains Xylene (mixed isomers) Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data.

#### Sensitization to material

: Not expected to be a skin sensitizer.  
Not expected to be a respiratory sensitizer.

#### Specific target organ effects

: Eyes, skin, respiratory system, digestive system, central nervous system, blood system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

#### Classification

Specific target organ toxicity, single exposure Category 3 May cause drowsiness and dizziness. May cause respiratory irritation.

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 8 of 14

## SAFETY DATA SHEET

**Medical conditions aggravated by overexposure**

: Pre-existing skin, eye, respiratory and central nervous system disorders.

**Synergistic materials**

: None reported by the manufacturer.

**Toxicological data**

: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC<sub>50</sub>(4hr)</u> <u>inh, rat</u>	<u>LD<sub>50</sub></u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Dipropylene glycol methyl ether	> 3 mg/L (mist) (No mortality)	5120 mg/kg	9480 mg/kg
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethyl benzene	24 mg/L	23 000 mg/kg	>3160mg/kg
Trimethylbenzenes	18 - 24mg/kg (based on similar substances)	8970 mg/kg	>3160mg/kg (based on similar substances)
Xylene (mixed isomers)	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
Cumeme	8000 ppm; 39 mg/L	2260 mg/kg	10 627 mg/kg

**Other important toxicological hazards**

: None known or reported by the manufacturer.

### SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

: No data is available on the product itself.  
 See the following tables for individual ingredient ecotoxicity data.

**Ecotoxicity data:**

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Dipropylene glycol methyl ether	34590-94-8	> 10,000 mg/L (Fathead minnow)	N/Av	None.
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.
1,2,4-Trimethylbenzene	95-63-6	7.19 - 8.28 mg/L (Fathead minnow)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.
Trimethylbenzenes	25551-13-7	7.72mg/L (Fathead minnow) (Read-across)	N/Av	None.
Xylene (mixed isomers)	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Cumeme	98-82-8	4.5mg/L (Rainbow trout)	0.38mg/L QSAR	None.





Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

### SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Dipropylene glycol methyl ether	34590-94-8	1919 mg/L (Daphnia magna)	≥ 0.5 mg/L	None.
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.
1,2,4-Trimethylbenzene	95-63-6	6.14 mg/L (Daphnia magna)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna)	0.4mg/L	None.
Trimethylbenzenes	25551-13-7	2.7mg/L Daphnia magna (Water flea) (Read-across)	0.4mg/L (Read-across)	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Cumeme	98-82-8	2.14 mg/L (Daphnia magna)	0.35mg/L	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Dipropylene glycol methyl ether	34590-94-8	> 969 mg/L/72hr (Green algae)	969 mg/L/72hr	None.
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av
1,2,4-Trimethylbenzene	95-63-6	N/Av	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	3.191mg/L QSAR	N/Av	None.
Trimethylbenzenes	25551-13-7	5.7mg/L/72hr (Green algae) (Read-across)	0.38mg/L/72hr (Read-across)	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Cumeme	98-82-8	1.29mg/L/72hr (Green algae)	0.73mg/L	None.

**Persistence and degradability**

: No data is available on the product itself.

**Bioaccumulation potential**

: No data is available on the product itself.

See the following data for ingredient information.



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 10 of 14

## SAFETY DATA SHEET

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Light aromatic solvent naphtha (CAS 64742-95-6)	2.1 - 6(calculated)	10 - 2500(calculated)
1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78	31 - 275
1,3,5-Trimethyl benzene (CAS 108-67-8)	3.6 - 3.93	23 - 328
Xylene (mixed isomers) (CAS 1330-20-7)	3.12 - 3.2	0.6 - 15
Cumene (CAS 98-82-8)	3.55 at 23 °C	224
Trimethylbenzenes (CAS 25551-13-7)	3.63	42 - 328
Dipropylene glycol methyl ether (CAS 34590-94-8)	0.0061	< 1

**Mobility in soil** : No data is available on the product itself.

**Other Adverse Environmental effects**

: The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

### SECTION 13. DISPOSAL CONSIDERATIONS

**Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

**Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.

**RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 11 of 14

## SAFETY DATA SHEET

### SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	NA1993	Combustible liquid, n.o.s. (Aromatic naphtha; Trimethylbenzene)	Combustible.	III	
<b>49CFR/DOT Additional information</b>	Not regulated for road or rail shipment if packaged in non-bulk containers (450 Litres or less each). The 'label' appearing here is the placard to be used for bulk shipments. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
TDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Naphtha)	9	III	
<b>TDG Additional information</b>	This material may be shipped as an exempted marine pollutant in accordance with TDG Section 1.45.1 and Special Provision 99.				
ICAO/IATA	UN3082	Environmentally hazardous substance, liquid, n.o.s. (Naphtha)	9	III	
<b>ICAO/IATA Additional information</b>	Refer to the appropriate Packing Instruction, prior to shipping this material. Review all State and Operator Variations, prior to shipping this material.				
IMDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Naphtha)	9	III	
<b>IMDG Additional information</b>	May be shipped as Limited Quantity when transported in containers no larger than 5.0 Litres; in packages not exceeding 30 kg gross mass.				

**Special precautions for user** : Keep away from heat, sparks and open flame - No smoking.

**Environmental hazards** : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
: Not available.

### SECTION 15 - REGULATORY INFORMATION

#### US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

**SAFETY DATA SHEET**

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Dipropylene glycol methyl ether	34590-94-8	Yes	None.	None.	No	N/Ap
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	N/Ap
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	1%
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Av	No	N/Ap
Trimethylbenzenes	25551-13-7	Yes	N/Ap	N/Ap	No	N/Ap
Xylene (mixed isomers)	1330-20-7	Yes	100 lb/ 45.4 kg	None.	Yes	1%
Cumeme	98-82-8	Yes	5000 lb/ 2270 kg	N/Ap	Yes	1%

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable; Eye irritation; Skin irritation ; Specific target organ toxicity, single exposure; Carcinogenicity ; Reproductive toxicity; Aspiration hazard . Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

**US State Right to Know Laws:**

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Dipropylene glycol methyl ether	34590-94-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No
Trimethylbenzenes	25551-13-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	No
Xylene (mixed isomers)	1330-20-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
Cumeme	98-82-8	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes

**Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). WHMIS Classification: See Section 2.

**International Information:**

Components listed below are present on the following International Inventory list:



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 13 of 14

## SAFETY DATA SHEET

Ingredients	CAS #	European EINECS	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Dipropylene glycol methyl ether	34590-94-8	252-104-2	Present	Present	(7)-97; (2)-426	KE-12230	Present	HSR001402
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
Trimethylbenzenes	25551-13-7	247-099-9	Present	Present	(3)-7; (3)-3427	KE-34408	Present	May be used as a single component chemical under an appropriate group standard.
Xylene (mixed isomers)	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Cumeme	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184

### SECTION 16. OTHER INFORMATION

#### Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- ATE: Acute Toxicity Estimate
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CNS: Central Nervous System
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency
- HMIS: Hazardous Materials Identification System
- HSDB: Hazardous Substances Data Bank
- IARC: International Agency for Research on Cancer
- Inh: Inhalation
- IMDG: International Maritime Dangerous Goods
- KECI: Korean Existing Chemicals Inventory
- KECL: Korean Existing Chemicals List
- LC: Lethal Concentration
- LD: Lethal Dose
- MA: Massachusetts
- MN: Minnesota
- MSHA: Mine Safety and Health Administration
- N/Ap: Not Applicable
- N/Av: Not Available
- NFPA: National Fire Protection Association
- NOEC: No observable effect concentration
- NTP: National Toxicology Program
- NJ: New Jersey



Hot 4-in-1 Heating Oil Treatment

SDS Preparation Date (mm/dd/yyyy): 04/02/2020

Page 14 of 14

## SAFETY DATA SHEET

NOEC: No observable effect concentration  
OECD: Organisation for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RI: Rhode Island  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

**References** : Material Safety Data Sheet from manufacturer.  
European Chemicals Agency, Classification Legislation, 2019.  
OECD - The Global Portal to Information on Chemical Substances - eChemPortal,

**Preparation Date (mm/dd/yyyy)**

: 04/02/2020

**Other special considerations for handling**

: Provide adequate information, instruction and training for operators.

**Prepared for:**

FPPF Chemical Company, Inc.  
117 West Tupper Street  
Buffalo, NY, USA 14201  
Telephone: 1-800-735-3773  
Please direct all enquiries to FPPF Chemical Company

### DISCLAIMER

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of FPPF Chemical Company, Inc.

**END OF DOCUMENT**