



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 1 of 17

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Total Power Diesel Fuel Treatment**

Other means of identification : 90420, 00344C

Recommended use of the chemical and restrictions on use

: Diesel fuel treatment  
Restrictions on use : Not intended for use by children.

Chemical family

: Mixture.

Name, address, and telephone number  
of the supplier:

**FPPF Chemical Company, Inc.**

117 West Tupper Street  
Buffalo, NY, USA 14201

Name, address, and telephone number of  
the manufacturer:

Refer to supplier

Supplier's Telephone # :

**24 Hr. Emergency Tel #** : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

### SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear to slightly hazy amber liquid. Solvent odor.

Most important hazards: Flammable liquid and vapor. May be ignited by open flames and sparks. Aspiration hazard. May cause respiratory irritation. May cause drowsiness or dizziness. Possible cancer hazard - contains material which may cause cancer.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazard classification:

Flammable liquid- Category 3

Carcinogen - Category 2

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Aspiration Toxicity - Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!



**Total Power Diesel Fuel Treatment**

**SDS Revision Date (mm/dd/yyyy): 04/02/2020**

Page 2 of 17

## SAFETY DATA SHEET

*Hazard statement(s)*

Flammable liquid and vapor.  
Suspected of causing cancer.  
May cause respiratory irritation.  
May cause drowsiness and dizziness.  
May be fatal if swallowed and enters airways.

*Precautionary statement(s)*

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical and ventilating equipment.  
Use non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing vapors or mists.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or doctor/physician if you feel unwell.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.  
In case of fire: Use water fog, dry chemical, CO<sub>2</sub> or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Dispose of contents/container in accordance with local regulation.

**Other hazards**

Other hazards which do not result in classification:

May be sensitive to static discharge. Burning produces obnoxious and toxic fumes.

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Light aromatic solvent naphtha	Aromatic solvent naphtha Solvent Naphtha (Petroleum) Light Aromatic	64742-95-6	30.0 - 60.0
Dipropylene glycol monomethyl ether	1-(2-Methoxypropoxy) -2-propanol DPGME	34590-94-8	10.0 - 30.0
Heavy aromatic solvent naphtha	Aromatic solvent naphtha Heavy Aromatic Naphtha	64742-94-5	1.0 - 5.0
1,2,4-Trimethylbenzene	Pseudocumene	95-63-6	1.0 - 5.0
1,3,5-Trimethyl benzene	Mesitylene Trimethylbenzol	108-67-8	1.0 - 5.0
2-Ethylhexyl nitrate	Nitric acid, 2-ethylhexyl ester Ethylhexyl nitrate	27247-96-7	1.0 - 5.0



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 3 of 17

## SAFETY DATA SHEET

Naphthalene	Moth balls Moth flakes Tar camphor	91-20-3	0.1 - 1.0
2-ethyl hexanol	2-ethylhexan-1-ol 2-Ethylhexyl alcohol 2EH	104-76-7	0.1 - 1.0
<b>The Solvent naphtha (petroleum), heavy aromatic component contains the following chemicals:</b>			
Xylene (mixed isomers)	Dimethylbenzene Methyltoluene Xylol	1330-20-7	<0.1
trimethylbenzene	Trimethylbenzene (mixed isomers) Methylxylenes	25551-13-7	<0.1
Cumene	Isopropyl benzene; Cumol, 2-Phenyl propane	98-82-8	<0.1
1,2,3-Trimethylbenzene	Benzene, 1,2,3-trimethyl-	526-73-8	<0.1

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

### SECTION 4. FIRST-AID MEASURES

#### Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Aspiration hazard. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only.
- Skin contact* : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: get medical advice/attention.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

#### Most important symptoms and effects, both acute and delayed

- : May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing. Symptoms include coughing, shortness of breath and wheezing. May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
- Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

#### Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

##### *Suitable extinguishing media*

- : Dry chemical, foam, carbon dioxide and water fog.

##### *Unsuitable extinguishing media*

- : Do not use a solid water stream as it may scatter and spread fire.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 4 of 17

## SAFETY DATA SHEET

### Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable liquid and vapour. Vapours may be heavier than air and may collect in confined and low-lying areas. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

### Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Liquids - Category 3

### Hazardous combustion products

- : Carbon oxides. Polycyclic aromatic hydrocarbons. Reactive hydrocarbons. Nitrogen oxides. Aldehydes. Other irritating fumes and smoke.

### Special protective equipment and precautions for firefighters

#### *Protective equipment for fire-fighters*

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

#### *Special fire-fighting procedures*

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply or any natural waterway. Dike for water control.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- : Evacuate personnel to safe areas. Keep all other personnel upwind and away from the spill/release. All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

**Environmental precautions** : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply.

### Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities.

### Special spill response procedures

- : In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887. If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).  
US CERCLA Reportable quantity (RQ): See section 15.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 5 of 17

## SAFETY DATA SHEET

### SECTION 7. HANDLING AND STORAGE

- Precautions for safe handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks and open flame - No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Avoid breathing mist or vapours. Wash thoroughly after handling. Do not ingest. Do not eat, drink, smoke or use cosmetics while working with this product. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials.
- Conditions for safe storage :** Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.
- Incompatible materials :** Strong oxidizing agents, Perchloric acid, Bases .

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Light aromatic solvent naphtha	N/Av	N/Av	N/Av	N/Av
Dipropylene glycol monomethyl ether	100 ppm (skin)	150 ppm (skin)	100 ppm (600 mg/m <sup>3</sup> ) (skin)	N/Av
Heavy aromatic solvent naphtha	N/Av	N/Av	500 ppm (as petroleum distillates, naphtha)	N/Av
1,2,4-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
1,3,5-Trimethyl benzene	25 ppm (trimethylbenzene isomers)	N/Av	25 ppm (trimethylbenzene isomers) (final rule limit)	N/Av
2-Ethylhexyl nitrate	N/Av	N/Av	N/Av	N/Av
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm (435 mg/m <sup>3</sup> )	N/Av
trimethylbenzene	25 ppm	N/Av	25 ppm (final rule limit)	N/Av
Cumene	50 ppm	N/Av	50 ppm ; 245 mg/m <sup>3</sup> (Skin)	N/Av
Naphthalene	10 ppm (skin)	N/Av	10 ppm ; 50 mg/m <sup>3</sup>	15ppm; 75mg/m <sup>3</sup>
2-ethyl hexanol	N/Av	N/Av	N/Av	N/Av
1,2,3-Trimethylbenzene	25 ppm (trimethylbenzene isomers)	N/Av	N/Av	N/Av



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 6 of 17

## SAFETY DATA SHEET

- Respiratory protection** : Use explosion-proof electrical and ventilating equipment. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.
- Respiratory protection** : If engineering controls and work practices are not effective in controlling exposure to this material, then wear suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.
- Skin protection** : Wear protective gloves/clothing. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye / face protection** : Wear eye/face protection. Safety glasses with side-shields or chemical splash goggles, depending on workplace standards.
- Other protective equipment** : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
- General hygiene considerations** : Avoid breathing mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Clear to slightly hazy amber liquid.
- Odour** : Solvent odor.
- Odour threshold** : N/Av
- pH** : N/Av
- Melting Point/Freezing point** : N/Av
- Initial boiling point and boiling range** : >149°C / 300°F
- Flash point** : 48.3°C / 119°F
- Flashpoint (Method)** : Tag closed cup
- Evaporation rate (BuAe = 1)** : Slower than n-butyl acetate
- Flammability (solid, gas)** : N/Av
- Lower flammable limit (% by vol.)** : N/Av
- Upper flammable limit (% by vol.)** : N/Av
- Oxidizing properties** : None known.
- Explosive properties** : N/Av
- Vapour pressure** : <4mm Hg @ 20°C
- Vapour density** : >1
- Relative density / Specific gravity** : 0.891
- Solubility in water** : Partially soluble.
- Other solubility(ies)** : N/Av
- Partition coefficient: n-octanol/water or Coefficient of water/oil distribution** : N/Av
- Auto-ignition temperature** : N/Av
- Decomposition temperature** : N/Av
- Viscosity** : N/Av



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 7 of 17

## SAFETY DATA SHEET

**Volatiles (% by weight)** : 90%(approximately)  
**Volatile organic Compounds (VOC's)**  
: N/Av  
**Absolute pressure of container**  
: N/Av  
**Flame projection length** : N/Av  
**Other physical/chemical comments**  
: None reported by the manufacturer.

### SECTION 10. STABILITY AND REACTIVITY

**Reactivity** : Not normally reactive.  
**Chemical stability** : Stable under normal conditions.  
**Possibility of hazardous reactions**  
: Hazardous polymerization will not occur.  
**Conditions to avoid** : Keep away from heat, sparks and flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Take precautionary measures against static discharge. Avoid contact with incompatible materials.  
**Incompatible materials** : Strong oxidizing agents, Perchloric acid, Bases.  
**Hazardous decomposition products**  
: None reported by the manufacturer. Refer also to hazardous combustion products, Section 5.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure:

**Routes of entry inhalation** : YES  
**Routes of entry skin & eye** : YES  
**Routes of entry Ingestion** : YES  
**Routes of exposure skin absorption**  
: YES

#### Potential Health Effects:

##### Signs and symptoms of short-term (acute) exposure

###### *Sign and symptoms Inhalation*

: Inhalation may cause respiratory irritation and central nervous system depression. Symptoms include: Upper respiratory irritation, coughing, sneezing, staggering gait, giddiness, drowsiness, slurred speech, nausea, and possible nervous system depression.

###### *Sign and symptoms ingestion*

: Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. May be fatal if swallowed and enters airways. Aspiration hazard - material may cause lung inflammation or damage if it enters lungs through vomiting or swallowing.

###### *Sign and symptoms skin*

: May cause drying or defatting of the skin.

###### *Sign and symptoms eyes*

: Direct eye contact may cause slight or mild, transient irritation.

##### Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

##### Mutagenicity

: Not expected to be mutagenic in humans.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 8 of 17

## SAFETY DATA SHEET

**Carcinogenicity** : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification :  
Carcinogenicity- Category 2  
Suspected of causing cancer.

Contains Naphthalene. Naphthalene is classified as carcinogenic by IARC (Group 2B) and NTP (Group 2 - Reasonably anticipated).

**Reproductive effects & Teratogenicity**

: Not classifiable as a reproductive toxin.

**Sensitization to material** : Not expected to be a skin sensitizer.  
Not expected to be a respiratory sensitizer.

**Specific target organ effects** : Eyes, skin, respiratory system, digestive system, central nervous system, blood system.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification  
Specific target organ toxicity, single exposure -Category 3  
May cause drowsiness and dizziness.  
May cause respiratory irritation.

Not classified as specific target organ toxicity-repeated exposure.

**Medical conditions aggravated by overexposure**

: Pre-existing skin, eye, respiratory and central nervous system disorders.

**Synergistic materials** : None reported by the manufacturer.

**Toxicological data** : The calculated ATE values for this mixture are:  
ATE inhalation (vapours) =35.06mg/L/4H

See below for individual ingredient acute toxicity data.





Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 9 of 17

## SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC<sub>50</sub>(4hr)</u> <u>inh, rat</u>	<u>LD<sub>50</sub></u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Light aromatic solvent naphtha	>17.7mg/L/4H (vapour)	8400 mg/kg	>3160 mg/kg
Dipropylene glycol monomethyl ether	> 3 mg/L (mist) (No mortality)	5120 mg/kg	9480 mg/kg
Heavy aromatic solvent naphtha	> 17.1 mg/L/4 hours	> 6000 mg/kg	> 3160 mg/kg
1,2,4-Trimethylbenzene	18 mg/L	5000 mg/kg	> 3160 mg/kg
1,3,5-Trimethyl benzene	24 mg/L (vapour)	23 000 mg/kg	> 3160 mg/kg
2-Ethylhexyl nitrate	> 14 mg/L	> 9600 mg/kg	> 4800 mL/kg
Naphthalene	No information available.	490 mg/kg	>20,000 mg/kg
2-ethyl hexanol	≥ 1.2, < 5.3 mg/L (aerosol)	2052 mg/kg	> 3000 mg/kg (No mortality)
<b>The Solvent naphtha (petroleum), heavy aromatic component contains the following chemicals:</b>			
Xylene (mixed isomers)	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
trimethylbenzene	18 - 24 mg/L (vapour)	8970 mg/kg	> 3160 mg/kg
Cumene	8000 ppm; (39 mg/L) (vapor)	2260 mg/kg	10 627 mg/kg
1,2,3-Trimethylbenzene	N/Av	N/Av	N/Av

### Other important toxicological hazards

: None known or reported by the manufacturer.

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

: Toxic to aquatic life with long lasting effects. See the following tables for individual ingredient ecotoxicity data.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

## SAFETY DATA SHEET

**Ecotoxicity data:**

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	9.22 mg/L (Rainbow trout)	N/Av	None.
Dipropylene glycol monomethyl ether	34590-94-8	> 10,000 mg/L (Fathead minnow)	N/Av	None.
Heavy aromatic solvent naphtha	64742-94-5	3.6 mg/L (Rainbow trout)	N/Av	None.
1,2,4-Trimethylbenzene	95-63-6	7.72 mg/L (Fathead minnow)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	12.52 mg/L (Goldfish)	N/Av	None.
2-Ethylhexyl nitrate	27247-96-7	2 mg/L (Zebra fish)	N/Av	None.
Xylene (mixed isomers)	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
trimethylbenzene	25551-13-7	7.72 mg/L (Fathead minnow) (Read-across)	N/Av	None.
Cumene	98-82-8	4.5 mg/L (Rainbow trout)	0.38mg/L QSAR	None.
Naphthalene	91-20-3	0.96 mg/L (pink salmon)	0.12mg/L (40 days) (pink salmon)	None.
2-ethyl hexanol	104-76-7	17.1 mg/L (Golden orfe)	N/Av	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Light aromatic solvent naphtha	64742-95-6	6.16 mg/L (Daphnia magna)	N/Av	None.
Dipropylene glycol monomethyl ether	34590-94-8	1919 mg/L (Daphnia magna)	≥ 0.5 mg/L	None.
Heavy aromatic solvent naphtha	64742-94-5	1.1 mg/L Water flea	N/Av	None.
1,2,4-Trimethylbenzene	95-63-6	3.6mg/L (Daphnia magna)	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	6 mg/L (Daphnia magna)	0.4mg/L	None.
2-Ethylhexyl nitrate	27247-96-7	> 12.6 mg/L (Daphnia magna)	N/Av	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
trimethylbenzene	25551-13-7	2.7 mg/L (Daphnia magna) (Read-across)	0.4 mg/L (Read-across)	None.
Cumene	98-82-8	2.14 mg/L/24hr (Daphnia magna)	0.35mg/L	None.
Naphthalene	91-20-3	3.4 mg/L/ Water flea	0.6mg/L	None.
2-ethyl hexanol	104-76-7	39 mg/L (Daphnia magna)	N/Av	None.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 11 of 17

## SAFETY DATA SHEET

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Light aromatic solvent naphtha	64742-95-6	N/Av	N/Av	N/Av
Dipropylene glycol monomethyl ether	34590-94-8	> 969 mg/L/72hr (Green algae)	969 mg/L/72hr	None.
Heavy aromatic solvent naphtha	64742-94-5	7.2 mg/L/72 hours (Green algae)	0.22 mg/L/72 hours (Green algae)	None.
1,2,4-Trimethylbenzene	95-63-6	2.356mg/L/96hr QSAR	N/Av	None.
1,3,5-Trimethyl benzene	108-67-8	3.191 mg/L/96hr (Green algae) (QSAR)	N/Av	None.
2-Ethylhexyl nitrate	27247-96-7	1.57 mg/L/72hr (Green algae)	12.6 mg/L/72hr	None.
Xylene (mixed isomers)	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
trimethylbenzene	25551-13-7	5.7 mg/L/72hr (Green algae) (Read-across)	0.38 mg/L/72hr (Read-across)	None.
Cumene	98-82-8	1.29 mg/L/72hr (Green algae)	0.73mg/L	None.
Naphthalene	91-20-3	0.4mg/L/72hr (Marine diatom)	N/Av	None.
2-ethyl hexanol	104-76-7	11.5 mg/L/72hr (Green algae)	N/Av	None.

**Persistence and degradability**

: No data is available on the product itself.

**Bioaccumulation potential**

: No data is available on the product itself.

See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Light aromatic solvent naphtha (CAS 64742-95-6)	2.1 - 6(calculated)	10 - 2500
Naphthalene (CAS 91-20-3)	3.7	427
1,2,4-Trimethylbenzene (CAS 95-63-6)	3.78	31 - 275
Xylene (mixed isomers) (CAS 1330-20-7)	3.12 - 3.2	50 - 58
Heavy aromatic solvent naphtha (CAS 64742-94-5)	2.9 - 6.1	No information available.
1,3,5-Trimethyl benzene (CAS 108-67-8)	3.6 - 3.93	23 - 328
2-Ethylhexyl nitrate (CAS 27247-96-7)	5.24	No information available.
trimethylbenzene (CAS 25551-13-7)	3.63	42 - 328
Cumene (CAS 98-82-8)	3.55 at 23 °C	224
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	0.0061	< 1
2-ethyl hexanol (CAS 104-76-7)	2.9	30

**Mobility in soil**

: No data is available on the product itself.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 12 of 17

## SAFETY DATA SHEET

### Other Adverse Environmental effects

- : The ecological characteristics of this product have not been fully investigated. Contains material that may be harmful in the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

### SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

### SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha )	3	III	
<b>49CFR/DOT Additional information</b>	Not regulated for road or rail shipment if packaged in non-bulk containers (450 L / 119 Gallons or less each). Refer to 49 CFR Section 173.150. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
TDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic naphtha )	3	III	
<b>TDG Additional information</b>	This material may be shipped as non-regulated material when in small means of containment (<450 Litres), provided the requirements of TDG section 1.33 are met. This product meets the criteria for an environmentally hazardous material according to the IMDG Code.				
ICAO/IATA	UN1993	Flammable liquid, n.o.s. (Aromatic Naphtha)	3	III	
<b>ICAO/IATA Additional information</b>	Refer to ICAO/IATA Packing Instruction				
IMDG	UN1993	FLAMMABLE LIQUID, N.O.S. (Aromatic Naphtha)	3	III	
<b>IMDG Additional information</b>	Consult the IMDG regulations for exceptions.				

- Special precautions for user** : Keep away from heat, sparks and open flame - No smoking.
- Environmental hazards** : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.
- Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 13 of 17

## SAFETY DATA SHEET

### SECTION 15 - REGULATORY INFORMATION

#### US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	<u>CAS #</u>	<u>TSCA Inventory</u>	<u>CERCLA Reportable Quantity (RQ) (40 CFR 117.302):</u>	<u>SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:</u>	<u>SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical</u>	
					<u>Toxic Chemical</u>	<u>de minimus Concentration</u>
Light aromatic solvent naphtha	64742-95-6	Yes	N/Ap	N/Ap	No	N/Ap
Dipropylene glycol monomethyl ether	34590-94-8	Yes	None.	None.	No	N/Ap
Heavy aromatic solvent naphtha	64742-94-5	Yes	N/Ap	N/Av	No	N/Ap
1,2,4-Trimethylbenzene	95-63-6	Yes	N/Ap	N/Ap	Yes	1%
1,3,5-Trimethyl benzene	108-67-8	Yes	N/Ap	N/Ap	No	N/Ap
2-Ethylhexyl nitrate	27247-96-7	Yes	N/Ap	N/Ap	No	N/Ap
Xylene (mixed isomers)	1330-20-7	Yes	100 lb/ 45.4 kg	N/Ap	Yes	1%
trimethylbenzene	25551-13-7	Yes	N/Ap	N/Ap	No	N/Ap
Cumene	98-82-8	Yes	5000 lb/ 2270 kg	N/Ap	Yes	1%
Naphthalene	91-20-3	Yes	100 lb/ 45.4 kg	N/Av	Yes	0.1%
2-ethyl hexanol	104-76-7	Yes	None.	None.	No	N/Ap
1,2,3-Trimethylbenzene	526-73-8	Yes	N/Ap	N/Av	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable ; Aspiration hazard; Specific target organ toxicity, single exposure ; Carcinogenicity . Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

#### US State Right to Know Laws:

The following chemicals are specifically listed by individual States:



**Total Power Diesel Fuel Treatment**

**SDS Revision Date (mm/dd/yyyy): 04/02/2020**

**SAFETY DATA SHEET**

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Light aromatic solvent naphtha	64742-95-6	No	Not listed	No	No	No	No	No	No
Dipropylene glycol monomethyl ether	34590-94-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Heavy aromatic solvent naphtha	64742-94-5	No	Not listed	No	No	No	No	No	No
1,2,4-Trimethylbenzene	95-63-6	No	Not listed	No	Yes	Yes	Yes	Yes	No
1,3,5-Trimethyl benzene	108-67-8	No	Not listed	Yes	Yes	No	No	No	No
2-Ethylhexyl nitrate	27247-96-7	No	Not listed	No	No	No	No	No	No
Xylene (mixed isomers)	1330-20-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
trimethylbenzene	25551-13-7	No	Not listed	Yes	Yes	Yes	Yes	Yes	Yes
Cumene	98-82-8	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
Naphthalene	91-20-3	Yes	Carcinogen	Yes	Yes	Yes	Yes	Yes	Yes
2-ethyl hexanol	104-76-7	No	N/Ap	No	Yes	No	No	Yes	No
1,2,3-Trimethylbenzene	526-73-8	No	N/Ap	No	No	No	No	No	No

**Canadian Information:**

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL). WHMIS Classification: See Section 2.

**International Information:**

Components listed below are present on the following International Inventory list:



**Total Power Diesel Fuel Treatment**

SDS Revision Date (mm/dd/yyyy): 04/02/2020

**SAFETY DATA SHEET**

<u>Ingredients</u>	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Light aromatic solvent naphtha	64742-95-6	265-199-0	Present	Present	(9)-1698	KE-31662	Present	May be used as a single component chemical under an appropriate group standard.
Dipropylene glycol monomethyl ether	34590-94-8	252-104-2	Present	Present	(7)-97; (2)-426	KE-12230	Present	HSR001402
Heavy aromatic solvent naphtha	64742-94-5	265-198-5	Present	Present	(3)-7	KE-31656	Present	May be used as a single component chemical under an appropriate group standard.
1,2,4-Trimethylbenzene	95-63-6	202-436-9	Present	Present	(3)-7; (3)-3427	KE-34410	Present	HSR001382
1,3,5-Trimethyl benzene	108-67-8	203-604-4	Present	Present	(3)-7; (3)-3427	KE-34411	Present	HSR001229
2-Ethylhexyl nitrate	27247-96-7	248-363-6	Present	Present	(2)-3598	KE-13803	Present	May be used as a single component chemical under an appropriate group standard.
Xylene (mixed isomers)	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
trimethylbenzene	25551-13-7	247-099-9	Present	Present	(3)-7; (3)-3427	KE-34408	Present	May be used as a component in a product covered by a group standard, but is not approved for use as a chemical in its own right.
Cumene	98-82-8	202-704-5	Present	Present	(3)-32; (3)-22	KE-23957	Present	HSR001184
Naphthalene	91-20-3	202-049-5	Present	Present	(4)-311	KE-25545	Present	HSR001287
2-ethyl hexanol	104-76-7	203-234-3	Present	Present	(2)-217	KE-13766	Present	HSR001386
1,2,3-Trimethylbenzene	526-73-8	208-394-8	Present	Present	(3)-7; (3)-3427	KE-34409	Present	HSR004095

**SECTION 16. OTHER INFORMATION**

**Legend**

- : ACGIH: American Conference of Governmental Industrial Hygienists
- ATE: Acute Toxicity Estimate
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CNS: Central Nervous System
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%



Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 16 of 17

## SAFETY DATA SHEET

EINECS: European Inventory of Existing Commercial chemical Substances  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
Inh: Inhalation  
IMDG: International Maritime Dangerous Goods  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
MA: Massachusetts  
MN: Minnesota  
MSHA: Mine Safety and Health Administration  
N/Av: Not Available  
N/Av: Not Available  
NIOSH: National Institute of Occupational Safety and Health  
NOEC: No observable effect concentration  
NTP: National Toxicology Program  
NJ: New Jersey  
NOEC: No observable effect concentration  
OECD: Organisation for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RI: Rhode Island  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

### References

: Safety Data Sheets from manufacturer.  
OECD - The Global Portal to Information on Chemical Substances  
European Chemicals Agency, Classification Legislation

Preparation Date (mm/dd/yyyy) : 04/02/2020

### Other special considerations for handling

: Provide adequate information, instruction and training for operators.





FPPF Chemical Company, Inc.  
117 West Tupper Street  
Buffalo, NY, USA, 14201  
Telephone: (800) 735-3773

---

Total Power Diesel Fuel Treatment

SDS Revision Date (mm/dd/yyyy): 04/02/2020

Page 17 of 17

## **SAFETY DATA SHEET**

### **Prepared for:**

FPPF Chemical Company, Inc.  
117 West Tupper Street  
Buffalo, NY, USA 14201  
Telephone: 1-800-735-3773  
Please direct all enquiries to FPPF Chemical Company

### **DISCLAIMER**

The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. FPPF Chemical Company, Inc expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission FPPF Chemical Company, Inc.

**END OF DOCUMENT**